elica elica.com



Illusion

Flush with the ceiling, this kitchen hood blends right into the room. Its design cleverly conceals the extraction system, which can turn on, adjust, and turn off by itself. Or through an app and voice assistant.

Design by Design Fabrizio Crisà

elica elica.com

Generic Data

WEIGHT (KG)

H30: 23,7kg NO MOTOR: 17,3kg H16: 19,5kg

ENERGY CLASS

Α

DUCT TRANSITION H30: 150mm

NO MOTOR: 150mm H16: 222x89 (int)mm

VENTING TYPE

Duct-out

FINISHING

Plasterboard (not included)+ Stainless

Steel Frame

MINIMUM DISTANCE FROM WALL UNIT INDUCTION/RADIANT HOB

H30: 60cm NO MOTOR: 65cm H16: 60cm

LIGHTING

Strip Led 2x14 W - 2700 K - 5000 K - 563

LUX

DIMENSIONS (CM)

100x50cm

MINIMUM DISTANCE FROM WALL

UNIT GAS HOB

70cm

ABSORPTION

H30: 298W NO MOTOR: 428W H16: 303W

Motor

MOTOR 1200

H30: 1200 H16: 1200

Extraction

AIRFLOW MIN-MAX

H30: 200m3/h - 770m3/h NO MOTOR: 230m3/h - 850m3/h

H16: 275m³/h - 720m³/h

NOISE LEVEL MIN-MAX

H30: 40db(A) - 53db(A) NO MOTOR: 25db(A) - 56db(A)

H16: 51db(A) - 68db(A)

CONTROLS

3S+2B Remote control