










Model Name	Asti	Palermo	Trento	Arezzo
Model Numbers	EAS422SS EAS428S1	EPR628S1	ETR134S1	EAR628S4 EAR134S4 EAR140S4 EAR146S4
Dimensions	22¼" W x 10¾" D x 9½" H 28¼" W x 10¾" D x 9½" H	28¼" W x 10¾" D x 9¼" H	34½" W x 18" D x 11½" H	28½" W x 22" D x 11½" H 34½" W x 22" D x 11½" H 40½" W x 22" D x 11½" H 46½" W x 22" D x 11½" H
Blower Type	400 CFM (3-speed)	600 CFM (3-speed)	1200 CFM (4-speed)	600 CFM (4-speed) - 28" 1200 CFM (4-speed) - 34", 40" & 46"
Blower Performance	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 400 CFM	Speed 1, 190 CFM Speed 1, 350 CFM Speed 1, 600 CFM	Speed 1, 380 CFM Speed 2, 660 CFM Speed 3, 950 CFM Speed 4, 1200 CFM	(28") - Speed 1, 90 CFM Speed 2, 330 CFM Speed 3, 490 CFM (34", 40", 46") - Speed 1, 380 CFM Speed 2, 660 CFM Speed 3, 950 CFM Speed 4, 1200 CFM
CFM Reduction	Yes / KITO2748	No	No	No
Noise (sones)	Min: 1.5, Max: 5.9	Min: 2.1, Max: 6.0	Min: 2.05, Max: 7.5	Min: 2.0, Max: 9.6 (28") Min: 2.05, Max: 7.5 (34", 40", 46")
Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Controls	Backlit Electronic Push Button	Stainless Steel Push Button	Fully Retractable Rotating Knobs w/Blue Backlighting	Fully Retractable Rotating Knobs w/Blue Backlighting
Illumination	2 LED, 2.1 watts	2 Premium LED, 2.5 watts	2 Consumer Replaceable LED, 7.5 watts	2 LED, 7.5 watts (28", 34") 4 LED, 7.5 watts (40", 46") <small>*Consumer Replaceable</small>
Filter Type	Dishwasher-Safe Anodized Aluminum Mesh (1w/22", 2w/28")	2 Dishwasher-Safe, Stainless Steel Baffle Slot Grease Filter	Dishwasher-Safe, Professional Stainless Steel	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter
Duct Transition	6" Round with Back Draft Damper (top only)	6" Round with Back Draft Damper (top only)	10" Round with Back Draft Damper (top only)	10" Round with Back Draft Damper (top only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted Installation Only	
Electrical	120 V - 60 Hz 340 Wattage	120 V - 60 Hz 260 Wattage	120 V - 60 Hz 1000 Wattage	120 V - 60 Hz 1000 Wattage
Stainless Steel Liner Kit	Available in 30" or 36" widths	Available in 30" or 36" widths		
Optional Blower	No	No	1200 CFM Inline or 1200 CFM External	1200 CFM Inline or 1200 CFM External
Page	120	68	94	92





				
Model Name	Nemi	TT	Allasio	Bellagio
Model Numbers	ENM230S1 ENM236S1 ENM230WT ENM230BL	ETT424SS	EAL330S1 EAL336S1 EAL330WT EAL330BL	EBL430SS EBL436SS EBL430WT
Dimensions	30" W x 18 3/4" D x 5" H 36" W x 18 3/4" D x 5" H	23 9/16" W x 17 1/8" D x 1 9/16" H	30" W x 20" D x 4 3/4" H 36" W x 20" D x 4 3/4" H	30" W x 20" D x 4 3/4" H 36" W x 20" D x 4 3/4" H 30" W x 20" D x 4 3/4" H
Blower Type	280 CFM(3-speed)	400 CFM(3-speed)	300 CFM(3-speed)	430 CFM(4-speed)
Blower Performance	Speed 1, 110 CFM Speed 2, 220 CFM Speed 3, 280 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 400 CFM	Speed 1, 120 CFM Speed 2, 210 CFM Speed 3, 300 CFM	Speed 1, 160 CFM Speed 2, 240 CFM Speed 3, 310 CFM Speed 4, 430 CFM
CFM Reduction	No	Yes/ KIT02748	No	Yes
Noise (sones)	Min: 1.5, Max: 4.7	Min: 1.5, Max: 5.9	Min: 1.85, Max: 4.2	Min: 1.4, Max: 7.1
Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Controls	Backlit Electronic Push Button	Hidden Electronic Touch Controls	Backlit Electronic Push Button Controls	Multi-function Electronic with LCD Display
Illumination	2 LED, 2.1 watts	2 LED, 2.1 watts	2 LED, 2.1 watts	2 Halogen, 50 watts
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh	2 Dishwasher-Safe, Anodized Aluminum Mesh	2 Dishwasher-Safe, Anodized Mesh Grease Filter	2 Dishwasher-Safe, Anodized Aluminum Mesh Grease Filter
Duct Transition	3" x 1/4" x 10" with Back Draft Damper (Top and Rear)	6" Round (Top Only)	3 1/4" x 10" with Back Draft Damper (Top and Rear)	3 1/4" x 10" with Back Draft Damper (Top and Rear)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted or Recirculating	Ducted or Recirculating
Electrical	120 V - 60 Hz 210 Wattage	120 V - 60 Hz 280 Wattage	120 V - 60 Hz 360 Wattage	120 V - 60 Hz 445 Wattage
Page	116	114	115	64





			
Model Name	Aria	Modena	Glide
Model Numbers	EAI430SS EAI436SS	EMD530S3 EMD536S3	EGL430S1 EGL436S1
Dimensions	30" W x 20" D x 4 ¾" H 36" W x 20" D x 4 ¾" H	30" W x 20" D x 9" H 36" W x 20" D x 9" H	30"W x 11 ½-19 ¾" D x 2 ¾" H 36"W x 11 ½-19 ¾" D x 4 ¾" H
Blower Type	430 CFM (4-speed)	520 CFM (4-speed)	450 CFM (4-speed)
Blower Performance	Speed 1, 160 CFM Speed 2, 240 CFM Speed 3, 310 CFM Speed 4, 430 CFM	Speed 1, 170 CFM Speed 2, 280 CFM Speed 3, 430 CFM Speed 4, 520 CFM	Speed 1, 110 CFM Speed 2, 200 CFM Speed 3, 300 CFM Speed 4, 400 CFM
CFM Reduction	Yes	Yes	No
Noise (sones)	Min: 1.1, Max: 4.7	Min: 1.73, Max: 6.0	Min: 0.7, Max: 5.2
Finish	Stainless Steel + Black Glass	Stainless Steel + Black Glass	Stainless Steel + Glass
Controls	Touch Control 3 Speed + Booster	Touch Controls 3 Speed + Booster	Backlit Electronic Push Button Controls
Illumination	2 Premium LED Dimmable Lights, 2.5 watts	2 Premium LED Dimmable Lights, 2.5 watts	2 LED, 3 watts
Filter Type	2 Dishwasher-Safe, Stainless Steel Baffle Slot Filter	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	1 Dishwasher-Safe, Stainless Steel Mesh Filter
Duct Transition	3 ¼" x 10" with Back Draft Damper (Top or Rear)	3 ¼" x 10" with Back Draft Damper (Top or Rear)	6" Round (Top only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted or Recirculating
Electrical	120 V - 60 Hz 445 Wattage	120 V - 60 Hz 550 Wattage	120 V - 60 Hz 270 Wattage
Page	60	62	111





			
Model Name	Sora	Cervinia	Calabria
Model Numbers	ESR430S1 ESR436S1	ECV630S3 ECV636S3	ECL630S4 ECL136S4 ECL142S4 ECL148S4
Dimensions	30"W x 23"D x 10"H 36"W x 23"D x 10"H	30"W x 23"D x 11 1/32"H 36"W x 23"D x 11 1/32"H	30"W x 25"D x 18"H 36"W x 25"D x 18"H 42"W x 25"D x 18"H 48"W x 25"D x 18"H
Blower Type	400 CFM(2-speed)	600 CFM(4-speed)	600 CFM(4-speed) - 30" 1200 CFM (4-speed) - (36", 42", 48")
Blower Performance	Speed 1, 160 CFM Speed 2, 400 CFM	Speed 1, 170 CFM Speed 2, 280 CFM Speed 3, 440 CFM Speed 4, 600 CFM	(30") - Speed 1, 205 CFM Speed 2, 350 CFM Speed 3, 510 CFM Speed 4, 600 CFM (36", 42", 48") - Speed 1, 375 CFM Speed 2, 640 CFM Speed 3, 940 CFM Speed 4, 1200 CFM
CFM Reduction	Yes / KIT02748	No	No
Noise (sones)	Min: 1.5, Max: 5.9	Min: 2.34, Max: 7.0	Min: 2.01, Max: 6.0 (30") Min: 3.1, Max: 7.7 (36", 42", 48")
Finish	Stainless Steel	Stainless Steel	Stainless Steel
Controls	Rocker Switch Controls	Fully Retractable Rotating Knobs w/ Blue Backlighting	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	2 LED Lamps, 2.1 watts	2 Consumer Replaceable LED, 7.5 watts	2 Consumer Replaceable LED, 7.5 watts
Filter Type	2 Dishwasher-Safe, Stainless Steel Baffle Slot Grease Filter	2 Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter 2 (30", 36", 42"), 3 (48")
Duct Transition	3 1/4" x 10" with Back Draft Damper (Top and Rear)	3 1/4" x 10" with Back Draft Damper (Top and Rear)	10" Round with Back Draft Damper (Top and Rear)
Installation Type	Ducted or Recirculating	Ducted Installation Only	Ducted Installation Only
Electrical	120 V - 60 Hz 340 Wattage	120 V - 60 Hz 550 Wattage	120 V - 60 Hz 550 Wattage
Page	121	90	88





SPECS




Chimney Hoods




				
Model Name	Volterra	Varna	Varna Black	Pilato
Model Numbers	EVL424SS EVL430SS EVL436SS	EVR630S2 EVR636S2	EVR630BL EVR636BL	EPL630S1 EPL636S1
Dimensions	24"W x 19 5/8"D x 10 1/4"H 30"W x 19 5/8"D x 10 1/4"H 36"W x 19 5/8"D x 10 1/4"H	30"W x 19 11/16"D x 10 1/4"H 36"W x 19 11/16"D x 10 1/4"H	30"W x 19 11/16"D x 10 1/4"H 36"W x 19 11/16"D x 10 1/4"H	30"W x 21 1/2"D x 10 1/4"H 36"W x 21 1/2"D x 10 1/4"H
Blower Type	400 CFM (3-speed)	600 CFM (4-speed)	600 CFM (4-speed)	600 CFM (4-speed)
Blower Performance	Speed 1, 160 CFM Speed 2, 285 CFM Speed 3, 400 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 475 CFM Speed 4, 600 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 475 CFM Speed 4, 600 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 475 CFM Speed 4, 600 CFM
CFM Reduction	Yes/ KIT02748	Yes	Yes	No
Noise (sones)	Min: 0.83, Max: 6.0	Min: 1.93, Max: 6.0	Min: 1.93, Max: 6.0	Min: 1.7, Max: 8.2
Finish	Stainless Steel	Stainless Steel + Black Glass	Black Stainless Steel + Black Glass	Stainless Steel
Controls	Backlit Electronic Push Button	Touch Controls 3 Speed + Booster	Touch Controls 3 Speed + Booster	Multi-function Electronic with LCD Display
Illumination	2 LED lamps, 2,1 watts	2 Premium Dimmable Lights, 2.5 watts	2 Premium LED Dimmable Lights, 2.5 watts	2 Halogen Lamps, 40 watts
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh (2w/24", 30" & 3w/36")	Dishwasher-Safe, Anodized Aluminum Mesh (2w/30" & 3w/36")	Dishwasher-Safe, Anodized Aluminum Mesh (2w/30" & 3w/36")	Dishwasher-Safe, Anodized Aluminum Mesh (2w/30" & 3w/36")
Duct Transition	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted or Recirculating	Ducted or Recirculating
Electrical	120 V - 60 Hz 300 Wattage	120 V - 60 Hz 340 Wattage	120 V - 60 Hz 490 Wattage	120 V - 60 Hz 530 Wattage
Page	117	56	54	66

				
Model Name	Foglia	Lugano	Stoney	Leone
Model Numbers	EFG630S1 EFG636S1	ELG630S3 ELG636S3	EST630SS EST636SS	ELN630S2 ELN136S2 ELN142S2 ELN148S2
Dimensions	30" W x 20" D x 10" H 36" W x 20" D x 10" H	30" W x 19 1/16" D x 5" H 36" W x 19 1/16" D x 5" H	30" W x 19 7/8" D x 5" H 36" W x 19 7/8" D x 5" H	30" W x 24" D x 12 1/8" H 36" W x 24" D x 12 1/8" H 42" W x 24" D x 12 1/8" H 48" W x 24" D x 12 1/8" H
Blower Type	600 CFM (4-speed)	600 CFM (4-speed)	600 CFM (4-speed)	600 CFM (4-speed) - (30") 1200 CFM (4-speed) - (36", 42", 48") *1200 CFM inline and external blowers available
Blower Performance	Speed 1, 210 CFM Speed 2, 300 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM Black Stainless Steel + Black Glass	(30") - Speed 1, 205 CFM Speed 2, 350 CFM Speed 3, 510 CFM Speed 4, 600 CFM (30", 42", 48") - Speed 1, 375 CFM Speed 2, 640 CFM Speed 3, 940 CFM Speed 4, 1200 CFM
CFM Reduction	Yes	Yes	Yes	No
Noise (sones)	Min: 1.71, Max: 7.5	Min: 2.03, Max: 8.0	Min: 1.53, Max: 6.0	Min: 2.01, Max: 6.0 (30") Min: 3.21, Max: 7.7 (36", 42", 48")
Finish	Stainless Steel + Black Glass	Stainless Steel + Black Glass	Black Stainless Steel + Black Glass	Stainless Steel
Controls	Touch Controls 3 Speed + Booster	Touch Controls 3 Speed + Booster	Touch Controls 3 Speed + Booster (Sensor)	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	2 Premium LED Dimmable Lights, 2.5 watts	2 Premium LED Dimmable Lights, 2.5 watts	2 Premium LED Dimmable Lights, 2.5 watts	2 Consumer Replaceable LED, 7.5 watts
Filter Type	Dishwasher-Safe, Stainless Steel Micro Hole Grease Filter	Aluminum Mesh Filter + Perimeter Aspiration	Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters 1w/30", 2w/36" & 42", 3w/48"
Duct Transition	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top only)	8" Round with Back Draft Damper (Top only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted or Recirculating	Ducted Installation Only
Electrical	120 V - 60 Hz, 490 Wattage	120 V - 60 Hz, 530 Wattage	120 V - 60 Hz, 530 Wattage	120 V - 60 Hz, 800 Wattage
Page	58	72	42	80




				
Model Name	Toblino	Mezzano	Meteorite	Vavano
Model Numbers	ETB424SS ETB430S2 ETB436S2	EMZ630S3 EMZ636S3	EMT636SS	EVV636S1 EVV648S1
Dimensions	24" W x 19 5/8" D x 1 9/16" H 30" W x 19 5/8" D x 1 9/16" H 36" W x 19 5/8" D x 1 9/16" H	30" W x 19 1/16" D x 1 9/16" H 36" W x 19 1/16" D x 1 9/16" H	36" W x 17 1/8" D x 2 3/8" H	36" W x 24" D x 5" H 48" W x 24" D x 5" H
Blower Type	400 CFM (3-speed)	600 CFM (4-speed)	550 CFM (4-speed)	600 CFM (4-speed) (1200 CFM inline and external blowers available)
Blower Performance	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 400 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 192 CFM Speed 2, 310 CFM Speed 3, 450 CFM Speed 4, 550 CFM	Speed 1, 205 CFM Speed 2, 350 CFM Speed 3, 510 CFM Speed 4, 600 CFM
CFM Reduction	Yes/ KIT02748	Yes	No	No
Noise (sones)	Min: 0.78, Max: 6.0	Min: 1.73, Max: 6.0	Min: 1.7 Max: 7.0	Min: 3.21, Max: 7.7
Finish	Stainless Steel	Stainless Steel + Black Glass	Stainless Steel + Black Glass	Stainless Steel
Controls	Backlit Electronic Push Button	Touch Controls 3 Speed + Booster	Touch Controls 3 Speed + Booster (Sensor)	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	2 LED Lamps, 2.1 watts	2 Premium LED Dimmable Lights, 2.5 watts	Strip LED 7 Watts 2700-6000K - Tunable White	2 Consumer Replaceable LED, 7.5 watts
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh (2w/24" & 30", 3w/36")	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters 2 w/36", 3 w/48"
Duct Transition	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top Round 6")	8" Round with Back Draft Damper (Top only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted Installation Only	Ducted Installation Only
Electrical	120 V - 60 Hz 300 Wattage	120 V - 60 H 490 Wattage	120 V - 60 Hz 530 Wattage	120 V - 60 Hz 480 Wattage
Page	118	52	38	84

				
Model Name	Toblino	Mezzano	Meteorite	Vavano
Model Numbers	ETB424SS ETB430S2 ETB436S2	EMZ630S3 EMZ636S3	EMT636SS	EVV636S1 EVV648S1
Dimensions	24" W x 19 5/8" D x 1 9/16" H 30" W x 19 5/8" D x 1 9/16" H 36" W x 19 5/8" D x 1 9/16" H	30" W x 19 1/16" D x 1 9/16" H 36" W x 19 1/16" D x 1 9/16" H	36" W x 17 1/8" D x 2 3/8" H	36" W x 24" D x 5" H 48" W x 24" D x 5" H
Blower Type	400 CFM (3-speed)	600 CFM (4-speed)	550 CFM (4-speed)	600 CFM (4-speed) (1200 CFM inline and external blowers available)
Blower Performance	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 400 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 192 CFM Speed 2, 310 CFM Speed 3, 450 CFM Speed 4, 550 CFM	Speed 1, 205 CFM Speed 2, 350 CFM Speed 3, 510 CFM Speed 4, 600 CFM
CFM Reduction	Yes/ KIT02748	Yes	No	No
Noise (sones)	Min: 0.78, Max: 6.0	Min: 1.73, Max: 6.0	Min: 1.7 Max: 7.0	Min: 3.21, Max: 7.7
Finish	Stainless Steel	Stainless Steel + Black Glass	Stainless Steel + Black Glass	Stainless Steel
Controls	Backlit Electronic Push Button	Touch Controls 3 Speed + Booster	Touch Controls 3 Speed + Booster (Sensor)	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	2 LED Lamps, 2.1 watts	2 Premium LED Dimmable Lights, 2.5 watts	Strip LED 7 Watts 2700-6000K - Tunable White	2 Consumer Replaceable LED, 7.5 watts
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh (2w/24" & 30", 3w/36")	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters 2 w/36", 3 w/48"
Duct Transition	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top Round 6")	8" Round with Back Draft Damper (Top only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted Installation Only	Ducted Installation Only
Electrical	120 V - 60 Hz 300 Wattage	120 V - 60 H 490 Wattage	120 V - 60 Hz 530 Wattage	120 V - 60 Hz 480 Wattage
Page	118	52	38	84

			
Model Name	Salice	Stoney Island	Leone Island
Model Numbers	ESL636S3 ESL642S3	ESI636SS ESI642SS	ELI136S2 ELI142S2
Dimensions	36" W x 27" D x 5" H 42" W x 27" D x 5" H	36" W x 27" D x 5" H 42" W x 27" D x 5" H	36" W x 27" D x 12 ¾" H 42" W x 27" D x 12 ¾" H
Blower Type	600 CFM (4-speed)	600 CFM (4-speed)	1200 CFM (4-speed) (1200 CFM inline and external blowers available)
Blower Performance	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 180 CFM Speed 2, 300 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 375 CFM Speed 2, 640 CFM Speed 3, 940 CFM Speed 4, 1200 CFM
CFM Reduction	Yes Dimmable Lights, 2.5 watts	Yes	No
Noise (sones)	Min: 1.73, Max: 6.0	Min: 1.46, Max: 6.0	Min: 3.21, Max: 7.7
Finish	Stainless Steel + Black Glass	Stainless Steel + Black Glass	Stainless Steel
Controls	Touch Controls 3 Speed + Booster	Touch Controls 3 Speed + Booster	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	4 Premium LED Dimmable Lights, 2.5 watts	4 Premium LED Dimmable Lights, 2.5 watts	4 Consumable Replaceable LED, 7.5 watts
Filter Type	Aluminum Mesh Filter + Perimeter Aspiration	Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration	2 Dishwasher-Safe, 2 Professional Stainless Steel Angled Baffle Filter
Duct Transition	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top only)	8" Round with Back Draft Damper (Top only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted Installation Only
Electrical	120 V - 60 Hz 530 Wattage	120 V - 60 Hz 530 Wattage	120 V - 60 Hz 800 Wattage
Page	76	44	82

			
Model Name	Maggiore	Meteorite Island	Vavano Island
Model Numbers	EMG636S1 EMG642S1	EMI648SS	EVI642S1 EVI648S1
Dimensions	36" W x 19 11/16" D x 1 9/16" H 42" W x 19 11/16" D x 1 9/16" H	48" W x 24" D x 2 3/8" H	42" W x 24" D x 5" H
Blower Type	600 CFM (4-speed)	550 CFM (4-speed)	600 CFM (4-speed) (1200 CFM Inline and External blowers available)
Blower Performance	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 192 CFM Speed 2, 310 CFM Speed 3, 450 CFM Speed 4, 550 CFM	Speed 1, 205 CFM Speed 2, 350 CFM Speed 3, 510 CFM Speed 4, 600 CFM
CFM Reduction	Yes	No	No
Noise (sones)	Min: 1.73, Max: 6.0	Min: 1.7, Max: 7.0	Min: 3.21, Max: 7.7
Finish	Stainless Steel + Black Glass	Stainless Steel + Black Glass	Stainless Steel
Controls	Touch Controls 3 Speed + Booster	Touch Controls 3 Speed + Booster (Sensor)	Fully Retractable Rotating Knobs w/Blue Backlighting
Illumination	4 Premium LED Dimmable Lights, 2.5 watts	Strip LED 7 watts 2700-6000K, Tunable White	4 Consumer Replaceable LED, 7.5 watts
Filter Type	3 Dishwasher-Safe, Stainless Steel Microhole Filter	Dishwasher-Safe, Aluminum Grease Filter + Perimeter Aspiration	Dishwasher-Safe, 3 Professional Stainless Steel Angled Baffle Filters
Duct Transition	6" Round with Back Draft Damper (Top only)	6" Round with Back Draft Damper (Top only)	8" Round with Back Draft Damper (Top only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted Installation Only
Electrical	120 V - 60 Hz 426.2 Wattage	120 V - 60 Hz 530 Wattage	120 V - 60 Hz 480 Wattage
Page	74	40	86




Curved Glass Island






			
Model Name	Potenza	Como	Cingoli
Model Numbers	EPT430S2 EPT436S2	ECM630S3 ECM636S3	ECN636S3 ECN642S3
Dimensions	30" W x 19 5/8" D x 1 15/16" H 36" W x 19 5/8" D x 1 15/16" H	30" W x 19 11/16" D x 1 15/16" H 36" W x 19 11/16" D x 1 15/16" H	36" W x 25 3/16" D x 1 15/16" H 42" W x 25 3/16" D x 1 15/16" H
Blower Type	400 CFM (3-speed)	600 CFM (4-speed)	600 CFM (4-speed)
Blower Performance	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 400 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM
CFM Reduction	Yes/ KIT02748	Yes	Yes
Noise (sones)	Min: 0.91, Max: 5.9	Min: 2.36, Max: 6.0	Min: 2.36, Max: 6.0
Finish	Stainless Steel	Stainless Steel + Black Glass	Stainless Steel + Black Glass
Controls	Backlit Electronic Push Button	Touch Controls 3 Speed + Booster	Touch Controls 3 Speed + Booster
Illumination	2 LED, 2.1 watts	2 Premium LED, Dimmable Lights, 2.5 watts	2 Premium LED, Dimmable Lights, 2.5 watts
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh Filter	Dishwasher-Safe, Stainless Steel Microhole Filter	1 Dishwasher-Safe, Stainless Steel Microhole Grease Filter
Duct Transition	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)	6" Round with Back Draft Damper (Top Only)
Installation Type	Ducted or Recirculating	Ducted or Recirculating	Ducted or Recirculating
Electrical	120 V - 60 Hz 300 Wattage	120 V - 60 Hz 530 Wattage	120 V - 60 Hz 530 Wattage
Page	119	48	50



Ceiling

Down Draft

Outdoor

			
Model Name	Siena	Rise	Capri
Model Numbers	ESNX43S1	ERS630S1 ERS636S1	ECP136SS ECP148SS
Dimensions	43" W x 27" D x 7 ¾" H	30" W x 12 ½" D x 14" H 36" W x 12 ½" D x 14" H	36" W x 32" D x 18" H 48" W x 32" D x 18" H
Blower Type	600 CFM In Line (4-speed)	600 CFM (4-speed)	1200 CFM (4-speed) Internal or external
Blower Performance	Speed 1, 160 CFM Speed 2, 280 CFM Speed 3, 470 CFM Speed 4, 600 CFM	Speed 1, 205 CFM Speed 2, 350 CFM Speed 3, 510 CFM Speed 4, 600 CFM	Speed 1, 375 CFM Speed 2, 640 CFM Speed 3, 940 CFM Speed 4, 1200 CFM
CFM Reduction	No	No	No
Noise (sones)		Min: 1.9, Max: 8.0	Min: 2.47, Max: 9.04
Finish	Stainless Steel	Stainless Steel	Corrosion Resistant Grade Stainless Steel
Controls	Remote Control	Rotative Touch Control	Fully Retractable Rotating Knobs w/Blue Backlighting
Illumination	4 LED, 2.5 watts		2 LED, 7.5 watts (36") 4 LED, 7.5 watts (48") <small>*Consumer Replaceable</small>
Filter Type	Dishwasher Safe Aluminum Mesh filter + Perimeter Aspiration	Perimeter Aspiration (Aluminum Mesh Filter Behind)	Dishwasher-Safe, Professional Stainless Steel 4 w/36", 6 w/48"
Duct Transition	5 way, 6" Round	6" Round with Back Draft Damper (Side)	10" Round with Back Draft Damper (Topn Only)
Installation Type	Ducted Installation Only	Ducted Installation Only	Ducted Installation Only
Electrical	120 V - 60 Hz 365 Wattage	120 V - 60 Hz 410 Wattage	120 V - 60 Hz 913 Wattage
Page	108	70	96

					
Model Name	Easy	Wave	Chrome	Twin	Star
Model Numbers	EES320SS EES320WT	EWV320SS	ECH623S1	ETP536SS	EST319GL
Dimensions	19 3/4" W x 19 3/4" D x 16 7/8" H	19 3/4" W x 19 3/4" D x 16 7/8" H	22 7/8" W x 17" D x 22 7/8" H	35 7/16" W x 19 11/16" D x 14 3/16" H	18 5/16" W x 18 5/16" D x 13 1/2" H
Blower Type	355 CFM (4-speed)	350 CFM (3-speed)	600 CFM (4-speed)	550 CFM (4-speed)	300 CFM (4-speed)
Blower Performance	Speed 1, 102 CFM Speed 2, 165 CFM Speed 3, 240 CFM Speed 4, 355 CFM	Speed 1, 110 CFM Speed 2, 220 CFM Speed 3, 350 CFM	Speed 1, 195 CFM Speed 2, 340 CFM Speed 3, 500 CFM Speed 4, 600 CFM	Speed 1, 200 CFM Speed 2, 325 CFM Speed 3, 450 CFM Speed 4, 450 CFM	Speed 1, 100 CF Speed 2, 175 CFM Speed 3, 250 CFM Speed 4, 300 CFM
CFM Reduction	No	No	No	No	No
Noise (sones)	Min: 1.65, Max: 5.0	Min: 0.3, Max: 3.8	Min: 0.7, Max: 4.8	Min: 0.31, Max: 4.3	Min: 0.31, Max: 4.1
Finish	Stainless Steel / White	Stainless Steel	Stainless Steel	Stainless Steel	Glass Crystals + Stainless Steel
Controls	Touch Control 3S + Booster	Electronic Backlit Push Button	Magic Wand	Magic Wand	Magic Wand
Illumination	3 LED, 5 watts	6 LED, 2 watts	2 LED, 3 watts	8 LED, 2 watts	1 LED, 2 watts
Filter Type	1 Dishwasher-Safe, Perimeter Aspiration + Aluminum Mesh Filter + 1 Carbon Long Life Filter	Dishwasher-Safe, Aluminum Mesh Grease Filter, 1 Long Life Carbon Filter	1 EDS Dishwasher-Safe, Anodized Aluminum Mesh Grease Filter	Dishwasher-Safe, 2 Aluminum Mesh Grease Filter, 2 Long Life Carbon Filter	1 Dishwasher-Safe, Aluminum Mesh Grease Filter + Long Life Carbon Filter
Installation Type	Recirculating Installation Only	Recirculating Installation Only	Ducted or Recirculating	Recirculating Installation Only	Recirculating Installation Only
Electrical	120 V - 60 Hz 460 Wattage	120 V - 60 Hz 320 Wattage	120 V - 60 Hz 490 Wattage	120 V - 60 Hz 320 Wattage	120 V - 60 Hz 320 Wattage
Page	102	106	110	107	104

		
Model Name	NikolaTesla	Golden
Model Numbers	ENT432BL	EGL324BL EGL430BL EGL536BL
Dimensions	32 1/16" W x 20 1/16" D x 8 1/4" H	23 3/4" W x 20 3/4" D x 2 1/4" H 29 3/4" W x 20 3/4" D x 2 1/4" H 35 3/4" W x 20 3/4" D x 2 1/4" H
Blower Type	400 CFM (4-speed)	
Blower Performance	Speed 1, 160 CFM Speed 2, 250 CFM Speed 3, 350 CFM Speed 4, 400 CFM (Booster)	
Noise (sones)	Min: 2.2, Max: 5.0	
Cooking Zones	4 (2,1 - 3,7 kW) - 7,1 x 7,9 inches	3 Cooking Zones + 1 Bridge Zone (24") 4 Cooking Zones + 1 Bridge Zone (30") 5 Cooking Zones + 2 Bridge Zones (36")
Heating Level	9 Levels + Booster	9 Levels + Booster
Finish	Black Glass	Black Glass
Controls	Slider Touch Control 3S + Booster Ventilation	Electronic Glass Touch with Finger Glide Function
Installation Type	Ducted or Recirculating Self Rimming or Flush Mounted	Self Rimming or Flush Mounted
Filter Specification	6 Layer Anodized Aluminum Mesh Grease Filter	
Electrical	208 - 240 V - 60 Hz 440 Watts at 3.3 Amps 240 V - 7.8 kW at 32.5 Amps 208 V - 7.1 kW at 34.1 Amps	(24" & 30") 208 - 240 V - 60 Hz 7.7 kW at 32.1 Amps 6.7 kW at 32.2 Amps (36") 208 - 240 V - 60 Hz 11.5 kW at 47.9 Amps 10 kW at 48.1 Amps
Page	22	28